

TECNA®



4 – 25 kg – 2000 mm wire – også tilgjengelig i ATEX-utførelse, Ex II 2GD c II T 85 °C (T6)

Art. nr.	Type	Kapasitet kg	Vekt kg	Lengde wire mm
24030047	9354	4 - 7	5	2000
24030710	9355	7 - 10	5,3	2000
24031014	9356	10 - 14	5,7	2000
24031418	9357	14 - 18	6,3	2000
24031822	9358	18 - 22	5,9	2000
24032255	9359	22 - 25	6,5	2000

10 – 105 kg – 2000 mm wire

Art. nr.	Type	Kapasitet kg	Vekt kg	Lengde wire mm
24041015	9361	10 - 15	8,7	2000
24041520	9362	15 - 20	9	2000
24042025	9363	20 - 25	9,3	2000
24042530	9364	25 - 30	10,1	2000
24043035	9365	30 - 35	10,1	2000
24043545	9366	35 - 45	11	2000
24044555	9367	45 - 55	11	2000
24045565	9368	55 - 65	11,9	2000
24046575	9369	65 - 75	12,7	2000
24047590	9370	75 - 90	15,7	2000
24049010	9371	90 - 105	16,6	2000

15 – 180 kg – 3000 mm wire

Art. nr.	Type	Kapasitet kg	Vekt kg	Lengde wire mm
24041015	9431	15 - 20	19,7	3000
24041520	9432	20 - 25	19,7	3000
24042025	9433	25 - 35	21,1	3000
24042530	9434	35 - 45	24,5	3000
24043035	9435	40 - 50	23,7	3000
24043545	9436	50 - 60	24,7	3000
24044555	9441	60 - 70	25,6	3000
24045565	9442	70 - 80	26,8	3000
24046575	9443	80 - 90	27,9	3000
24047590	9444	80 - 100	28,5	3000
24049010	9451	100 - 115	36,6	3000
24050160	9452	115 - 130	36,8	3000
24051378	9453	130 - 140	38,5	3000
24052595	9454	140 - 150	38,8	3000
24053813	9455	150 - 160	40,9	3000
24055030	9456	160 - 180	43,2	3000